

RESERVE STUDIES | INSURANCE APPRAISALS | WIND MITIGATION



Prepared Exclusively for Parkwood Square Villas Condominium

As of 5/24/2022 | FPAT File# MUD2216962



866.568.7853 | www.fpat.com



RECAPITULATION OF MITIGATION FEATURES For 5875 37th Ave N, Units 1-8

1. Building Code: Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1973 per Pinellas County

Property Appraiser.

2. Roof Covering: One or more roof coverings do not meet the minimum

requirements

Comments: No permit information was found for the tile roof covering. The flat

roof covering was replaced in 2021. The roof permit was confirmed and the permit number is 21-3000112. This roof was verified as not meeting the building code requirements outlined on the mitigation

affidavit.

3. Roof Deck Attachment: Other

Comments: Inspection verified a roof deck composed of lightweight concrete

gypsum panels supported by steel bar joists.

4. Roof to Wall Structural

Attachment:

Comments: Inspection verified a roof-wall connection composed of steel bar

joists structurally connected to the wall/support system.

5. Roof Geometry: Flat Roof

Comments: Inspection verified flat roof shape, refer to attached photographs.

6. SWR: No

Comments: SWR does not apply to metal bar joists with lightweight concrete

panels.

7. Opening Protection: None or Some Glazed Openings

Comments: No opening protection verified at the time of inspection.

Address Verification







Roof Construction



Roof Construction

Roof Construction

Roof Construction







Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 5/24/2022						
Owner Information						
Owner Name: Parkwood Square Villas Condominium Contact Person: Gloria Reed						
Address: 5875 37th Ave N, Units 1-8		Home Phone:				
City: St. Petersburg	Zip: 33710	Work Phone: (727) 726-8000				
County: Pinellas		Cell Phone:				
Insurance Company:		Policy #:				
Year of Home: 1973	# of Stories: 1	Email:				

Year of Home: 1973	# of Stories:	: 1	Email:	
NOTE: Any documentation used in accompany this form. At least one though 7. The insurer may ask add	photograph must ac	company this form	to validate each attribute m	arked in questions 3
 Building Code: Was the structure the HVHZ (Miami-Dade or Brownows) A. Built in compliance with the FE 3/1/2002: Building Permit Application of the HVHZ Only: Built in comprovide a permit application of the Linear Compression of the HVHZ Only: Built in Comprovide a permit application of the Linear Compression of the Linear Compre	ard counties), South I BC: Year Built . For oplication Date (MM/DD/ purpliance with the SI with a date after 9/1/1	Florida Building Cohomes built in 2002 'YYYY) FBC-94: Year Built 994: Building Perm	de (SFBC-94)? 1/2003 provide a permit applica	994, 1995, and 1996
 Roof Covering: Select all roof co OR Year of Original Installation/I covering identified. 2.1 Roof Covering Type: 				
[] 1. Asphalt/Fiberglass Shingle [X] 2. Concrete/Clay Tile [] 3. Metal [] 4. Built Up [X] 5. Membrane [] 6. Other	3/2/2021			[] [X] [] [] []
[] B. All roof coverings have a Mian	oplication date on or a ni-Dade Product App 1994 and before 3/1/2 do not meet the requir	of the roll of the	oof is original and built in 200 at time of installation OR (for original and built in 1997 or la	rrent at time of installation 44 or later. the HVHZ only) a roofing
3. Roof Deck Attachment : What is A. Plywood/Oriented strand board				mum of 24" inches o.c.) by

- A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

	A	
Inspectors Initials	0	Property Address 5875 37th Ave N, Units 1-8, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

1	2 psf.
	nforced Concrete Roof Deck.
	her: Steel bar joist
	nown or unidentified.
[] G. No	attic access.
	Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within of the inside or outside corner of the roof in determination of WEAKEST type) Nails
	[] Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or [] Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
3.51	•
Mini	al conditions to qualify for categories B, C, or D. All visible metal connectors are: []Secured to truss/rafter with a minimum of three (3) nails, and []Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
[] B. Cl	S
.	[] Metal connectors that do not wrap over the top of the truss/rafter, or [] Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
	le Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[X] E. S	[] Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or [] Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side. ructural Anchor bolts structurally connected or reinforced concrete roof.
[] F. Ot	
	nown or unidentified
[] H. No	attic access
	Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of t structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A. Hi	Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter:
[X] B. l	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[] C. Ot	er Roof Any roof that does not qualify as either (A) or (B) above.
[] A. SV	lary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) R (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the heathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling om water intrusion in the event of roof covering loss.
[X] B. I	
[] C. Uı	nown or undetermined.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least

Inspectors Initials Property Address 5875 37th Ave N, Units 1-8, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.			Glazed Openings				Non-Glazed Openings	
			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	N/A Not Applicable- there are no openings of this type on the structure		Х	Х	Х		Χ	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
	Opening Protection products that appear to be A or B but are not verified							
N	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection					Χ		

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115
 [] A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
 - □ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
 - ☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- [] B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - □ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - ☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- [] <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed of	openings classified as A	A. B. or	C in the table above.	or no Non-Glazed	openings exis

- ☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
- ☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 5875 37th Ave N, Units 1-8, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File #MUD2216962

[] <u>N. l</u>	Exterior Opening Protection (unverified shutter sys						
	protective coverings not meeting the requirements of "B" with no documentation of compliance (Level N		r systems	s that appear to meet Answer "A" or			
	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist						
	N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the table above						
	N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above					
[X] <u>X.</u>	None or Some Glazed Openings One or more Glazed	openings classified and Lev	vel X in tl	he table above.			
	MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov						
Quali	fied Inspector Name: John Felten	License Type: CBC		License or Certificate #: CBC1255984			
Inspe	ction Company: Felten Property Assessment Team		Phone:	866-568-7853			
Quali	fied Inspector – I hold an active license as a	: (check one)					
П Но	me inspector licensed under Section 468.8314, Florida Statute ining approved by the Construction Industry Licensing Board	s who has completed the statut		er of hours of hurricane mitigation			
	ilding code inspector certified under Section 468.607, Florida neral, building or residential contractor licensed under Section						
☐ Pro	ofessional engineer licensed under Section 471.015, Florida Sta	atutes.					
_	ofessional architect licensed under Section 481.213, Florida Sta						
	y other individual or entity recognized by the insurer as posses ification form pursuant to Section 627.711(2), Florida Statutes		ons to prop	erly complete a uniform mitigation			
Individ	luals other than licensed contractors licensed under S	Section 489.111, Florida S	tatutes, o	or professional engineer licensed			
under	Section 471.015, Florida Statues, must inspect the str	uctures personally and no	t throug	h employees or other persons.			
	ees under s.471.015 or s.489.111 may authorize a director conduct a mitigation verification inspection.	ect employee who possesse	s the req	uisite skill, knowledge, and			
experie							
I,	<u>John Felten</u> am a qualified inspector and l						
	etors and professional engineers only) I had my emplo gree to be responsible for his/her work.	yee (<u>brauley Silitii</u>) peri	orm the	mspection			
4114 1 4	gree to be responsible for mismer worm						
Qualifi	led Inspector Signature:Dat	e: <u>5/24/2022</u>					
An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the							
	oriate licensing agency or to criminal prosecution. (So						
certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally							
perfor	med the inspection.						
	Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that roof of identification was provided to me or my Authorized Representative.						
Signa	Signature: Date:						
	Date:						
	dividual or entity who knowingly provides or utters						
obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a							
misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)							
The defi	nitions on this form are for inspection purposes only and cannot b	e used to certify any product or	constructio	on feature as offering protection from			

Inspectors Initials Property Address 5875 37th Ave N, Units 1-8, St. Petersburg

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155