

RESERVE STUDIES | INSURANCE APPRAISALS | WIND MITIGATION



Prepared Exclusively for Parkwood Square Villas Condominium

As of 5/24/2022 | FPAT File# MUD2216962



Felten Property Assessment Team

866.568.7853 | www.fpat.com

SUPPORTING DOCUMENTION OF WINDSTORM MITIGATION FEATURES LOCATED AT: 5845 37th Ave N, Units 9-18

FPAT File #MUD2216962

RECAPITULATION OF MITIGATION FEATURES For 5845 37th Ave N, Units 9-18

1. Building Code: Unknown or does not meet the requirements of Answer A or B

Comments: The year of construction was verified as 1973 per Pinellas County

Property Appraiser.

2. Roof Covering: One or more roof coverings do not meet the minimum requirements

Comments: No permit information was found for the tile roof covering. The flat roof covering was replaced in 2012. The roof permit was confirmed and the permit number is 12-4000558. This roof was verified as not meeting the

building code requirements outlined on the mitigation affidavit.

3. Roof Deck Attachment: Other

Comments: Inspection verified a roof deck composed of lightweight concrete gypsum

panels supported by steel bar joists.

4. Roof to Wall Attachment: Structural

Comments: Inspection verified a roof-wall connection composed of steel bar joists

structurally connected to the wall/support system.

5. Roof Geometry: Flat Roof

Comments: Inspection verified flat roof shape, refer to attached photographs.

6. SWR: No

Comments: SWR does not apply to metal bar joists with lightweight concrete panels.

7. Opening Protection: None or Some Glazed Openings

Comments: No opening protection verified at the time of inspection.

Address Verification



Exterior Elevation

Roof Construction











Roof Construction



Roof Construction



Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 5/24/2022					
Owner Information					
Owner Name: Parkwood Square Villas Co	Contact Person: Gloria Reed				
Address: 5845 37th Ave N, Units 9-18		Home Phone:			
City: St. Petersburg	Zip: 33710	Work Phone: (727) 796-8000			
County: Pinellas		Cell Phone:			
Insurance Company:		Policy #:			
Year of Home: 1973	# of Stories: 1	Email:			

NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.

1.	Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in
	the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?
[]	A. Built in compliance with the FBC: Year Built . For homes built in 2002/2003 provide a permit application with a date after
	3/1/2002: Building Permit Application Date (MM/DD/YYYY)
[]	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996
	provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//
[X	C. Unknown or does not meet the requirements of Answer "A" or "B"

2. **Roof Covering:** Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.

2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
[] 1. Asphalt/Fiberglass Shingle				[]
[X] 2. Concrete/Clay Tile				[X]
[] 3. Metal				[]
[] 4. Built Up				[]
[] 5. Membrane				[]
[X] 6. Other Polyurethane foam	4/13/2012			[]

- [] A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
- B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
- [X] C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
- [] D. No roof coverings meet the requirements of Answer "A" or "B".
- 3. Roof Deck Attachment: What is the weakest form of roof deck attachment?
- [] A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
- [] B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
- [] C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

Inspectors Initials Property Address 5845 37th Ave N, Units 9-18, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

	or greater resista 182 psf.	nce than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
[] I	D. Reinforced Concre	ete Roof Deck.
	E. Other: Steel bar j	
	F. Unknown or unide	ntified.
[] (G. No attic access.	
	5 feet of the inside or	ment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within outside corner of the roof in determination of WEAKEST type)
[] F	top pla	s/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the te of the wall, or
	[] Meta	al connectors that do not meet the minimal conditions or requirements of B, C, or D
]	Minimal conditions	to qualify for categories B, C, or D. All visible metal connectors are:
		red to truss/rafter with a minimum of three (3) nails, and
		hed to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
[] E	3. Clips	
	[] Meta	al connectors that do not wrap over the top of the truss/rafter, or all connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail in requirements of C or D, but is secured with a minimum of 3 nails.
[] (C. Single Wraps	
	mi	etal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a nimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
[] I	D. Double Wraps	
	beam, o minim [] Meta	al Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a sum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or all connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on des, and is secured to the top plate with a minimum of three nails on each side.
[X]		or bolts structurally connected or reinforced concrete roof.
	F. Other:	
	G. Unknown or unide	entified
[] F	H. No attic access	
		at is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of runenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
[] A	A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: ; Total roof system perimeter:
[X]	B. Flat Roof	Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12: sq ft; Total roof area: sq ft
[] (C. Other Roof	Any roof that does not qualify as either (A) or (B) above.
[] A	A. SWR (also called a sheathing or foa	esistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the m adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling asion in the event of roof covering loss.

Inspectors Initials Property Address 5845 37th Ave N, Units 9-18, St. Petersburg

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Openings				Non-Glazed Openings	
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure		X	X	Χ		Χ	
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IN	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection	Χ				Χ		

- [] A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115
 - [] A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
 □ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
 - ☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- [] B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - □ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
- [] <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

Ш	C.1 All Non-Glaze	ed openings classif	ied as A, B, or C	in the table above,	or no Non-Glaze	d openings exist
---	-------------------	---------------------	-------------------	---------------------	-----------------	------------------

- ☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
- C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials Property Address 5845 37th Ave N, Units 9-18, St. Petersburg

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

FPAT File #MUD2216962

[] N. Exterior Opening Protection (unverified shutter sys protective coverings not meeting the requirements of "B" with no documentation of compliance (Level N is	Answer "A", "B", or C" or					
☐ N.1 All Non-Glazed openings classified as Level A, B, C, or	N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist					
☐ N.2 One or More Non-Glazed openings classified as Level I table above	O in the table above, and no No	n-Glazed openings classified as Level X in the				
☐ N.3 One or More Non-Glazed openings is classified as Leve	l X in the table above					
[X] X. None or Some Glazed Openings One or more Glazed		el X in the table above.				
1.						
MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov						
Qualified Inspector Name: John Felten	License Type: CBC	License or Certificate #: CBC1255984				
•						
Inspection Company: Felten Property Assessment Team		Phone: 866-568-7853				
Qualified Inspector – I hold an active license as a	(check one)					
☐ Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board at the Construction Indust	•	•				
 □ Building code inspector certified under Section 468.607, Florida □ General, building or residential contractor licensed under Section 						
☐ Professional engineer licensed under Section 471.015, Florida Sta	atutes.					
☐ Professional architect licensed under Section 481.213, Florida Sta	ntutes.					
Any other individual or entity recognized by the insurer as possess verification form pursuant to Section 627.711(2), Florida Statutes		ns to properly complete a uniform mitigation				
Individuals other than licensed contractors licensed under Sunder Section 471.015, Florida Statues, must inspect the str Licensees under s.471.015 or s.489.111 may authorize a direct experience to conduct a mitigation verification inspection. I, John Felten am a qualified inspector and licensees.	uctures personally and no ect employee who possesses	t through employees or other persons. s the requisite skill, knowledge, and				
contractors and professional engineers only) I had my emplo and I agree to be responsible for his/her work.						
R A						
Qualified Inspector Signature: Dat	e: <u>5/24/2022</u>					
An individual or entity who knowingly or through gross new is subject to investigation by the Florida Division of Insurar appropriate licensing agency or to criminal prosecution. (So certifies this form shall be directly liable for the misconduct performed the inspection.	nce Fraud and may be sub ection 627.711(4)-(7), Flori	ject to administrative action by the da Statutes) The Qualified Inspector who				
Homeowner to complete: I certify that the named Qualified residence identified on this form and that roof of identification						
Signature:	Date:					
An individual or entity who knowingly provides or utters obtain or receive a discount on an insurance premium to winder misdemeanor of the first degree. (Section 627.711(7), Florida.)	which the individual or ent					

The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.

Inspectors Initials Property Address 5845 37th Ave N. Units 9-18, St. Petersburg

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155